TR330 HIGH TRACTION SIDE SHIFTING TRIM MOWER





- ADAPTISHIFT™ SIDE SHIFTS REELS AT YOUR COMMAND
- ・TRUSTWORTHY Kubola ENGINE
- · ZERO MAINTENANCE WET PARKING BRAKES
- 3WD TRACTION SYSTEM

The TR330 high traction, side shifting trim mower is always consistent and dependable, with ADAPTISHIFT™ Reels at your command.

The TR330 is fitted with a trustworthy clean, green engine and has the narrowest width for easy transport and storage. This mower brings together comfort, manoeuvrability, cut quality and power, to make sure you can safely reach every blade of grass.

72" (1.83M)
OR 84" (2.13M)
featuring ADAPTISHIFT™ with
up to 12" (30.5cm) of offset

2.75" (9.5MM - 69.8MM)

(1.83 - 2.13HA) / HR (1.83 - 2.13M X 10KM / HR)





SINCERELY

For information and support: www.jacobsen.com / +44 (0) 1473 270 000 / +1-888-438-3946







TR330







Adaptishift™ side shifts reels at your command



Trustworthy, powerful engine



Contour following articulated reels

		100
REELS & BLADES		
NUMBER AND SIZE	3 x 26" (0.66m) or 30" (0.76m) reels; 7" (178mm) diameter	
BLADE MATERIAL	Hardened, high manganese carbon steel	
CUTTING UNIT LIFT	Armrest mounted joystick	
CUTTING FREQUENCY		
TRACTION, BRAKES & SPEED		
TRACTION DRIVE	Parallel-series "on demand" 3WD	
REEL DRIVE	Fixed displacement hydraulic	
HYDRAULIC SYSTEM	8.7 gal. (33L) capacity, full flow filtration (10 micron filter); GreensCare biodegradable oil	
SERVICE BRAKES	Dynamic braking through hydrostatic drive	
PARKING BRAKES	Service-free electronic wet disc	
STEERING	Hydraulic power steering with tilt wheel	
MOWING SPEED	6.2mph (10km/h)	
TRANSPORT SPEED	8.7mph (14km/h)	
WEIGHTS & DIMENSIONS		
WEIGHT (excluding fuel)	1664 - 2299lb (755 - 1043kg)	
LENGTH	97" (2.46m)	
OVERALL HEIGHT (including ROPS)	80" (2.04m)	
WHEELBASE	43.5" (1.36m)	
TRANSPORT WIDTH	83" (2.11m)	
WORKING WIDTH	83" (2.11m)	
WARRANTY		
MOWER WARRANTY	2 Years	
ACCESSORIES		
■ Slick tires ■ Verticuting reels Grass baskets	■ Light kit ■ Canopy ■ Backlap kit ■ Weight transfer kit	